

# MW100/MW101/MW102/MW500

Entry level, inexpensive pH/ORP/Temperature Portable Meters for fast and reliable results

- ATC
- MTC
- Points 2
- Self diagnostics
- CE



MW100, MW101, MW102 and MW500 are compact pH, ORP and Temperature Portable Meters with Faster Micro Processor. These handy and ergonomically designed portable meters are ideal for anyone working on a low budget and still requires fast and reliable measurements.





These portable meters are suitable for a wide range of applications, such as Educational, Agriculture and Horticulture, as well as water and environmental analysis.

These easier and faster to calibrate portable meters have a smaller, ergonomic and lighter case design. Other features include 100% larger and easier to read LCD Display and long battery life.

All meters are supplied with pH or ORP electrodes and calibration solutions.

- MW100 performs pH measurements with a 0.1 pH resolution and with manual temperature compensation.
- MW101 performs pH measurements with a 0.01 pH resolution and with manual temperature compensation.
- MW102 is a microprocessor based pH/Temperature meter with extended range (-2.00 to 16.00 pH), Automatic Temperature Compensation, automatic calibration in 2 points and  $\pm 0.02$  pH accuracy.
- MW500 performs ORP measurements with a range of  $\pm 1000$  mV.

## Specifications

		 <b>MW100 pH Meter</b>	 <b>MW101 pH Meter</b>	 <b>MW102 pH/Temp Meter</b>	 <b>MW500 ORP Meter</b>
Range	pH/ORP Temp	0.0 to 14.0 pH	0.00 to 14.00 pH	-2.00 to 16.00 pH -5 to 70°C	$\pm 1000$ mV
Resolution	pH/ORP Temp	0.1 pH	0.01 pH	0.01 pH 0.1°C	1 mV
Accuracy (@25°C)	pH/ORP Temp	$\pm 0.2$ pH	$\pm 0.02$ pH	$\pm 0.02$ pH $\pm 0.5^\circ\text{C}$	$\pm 5$ mV
Typical EMC Deviation	pH Temp			$\pm 0.02$ pH $\pm 0.5^\circ\text{C}$	
Temperature Compensation		N.A.	manual, 0 to 50°C	automatic, 0 to 70°C	
Calibration		manual, 2-point through offset and slope trimmers	manual, 2-point through offset and slope trimmers	automatic, at 1 or 2 points	
pH Electrode		SE220 (included)	SE220 (included)	SE220 (included)	
ORP Electrode					SE300 (included)
Temperature Probe				MA830R (included)	
Environment		0 to 50°C, max RH 95%	0 to 50°C, max RH 95%	0 to 50°C; max RH 95%	0 to 50°C; max RH 95%
Battery Type		1 x 9V alkaline (included)	1 x 9V alkaline (included)	1 x 9V alkaline (included)	1 x 9V alkaline (included)
Battery Life		approx. 300 hours of use	approx. 300 hours of use	approx. 300 hours of use	approx. 300 hours of use
Auto-off				after 8 minutes of non-use	
Dimensions		145 x 80 x 40 mm	145 x 80 x 40 mm	145 x 80 x 40 mm	145 x 80 x 40 mm
Weight		220 g (with battery)	220 g (with battery)	220 g (with battery)	220 g (with battery)

## Accessories

- M10004B pH 4.01 buffer solution 20 mL sachet (25 pcs)
- M10007B pH 7.01 buffer solution 20 mL sachet (25 pcs)
- M10010B pH 10.01 buffer solution 20 mL sachet (25 pcs)
- MA9004 pH 4.01 buffer solution, 230 mL bottle
- MA9007 pH 7.01 buffer solution, 230 mL bottle



- MA9015 Electrode storage solution, 230 mL
- MA9016 Electrode cleaning solution, 230 mL
- MA830R Temperature probe
- MA9020 200-275 mV ORP solution, 230 mL bottle
- SE220 pH electrode with BNC connector and 1 m cable
- SE300 Platinum ORP electrode with 1 m cable

## Ordering Information

MW100 and MW101 are supplied complete with a SE220 pH electrode, pH 7.01 20 mL sachet of calibration solution, calibration screwdriver, 9V battery and instructions.

MW102 is supplied complete with a SE220 pH electrode, MA830R stainless steel temperature probe, pH 4.01 and pH 7.01 20 mL sachet of calibration solution, 9V battery and instructions.

MW500 is supplied complete with a SE300 platinum electrode, 9V battery and instructions.



**FieldTech Solutions**

Tel - +61 3 9676 9664

37 Wirraway Drive, Port Melbourne, VIC.3207

Email - sales@fieldtechsoln.com