

CETCO® SET30

HIGH STRENGTH GYPSUM BASED CEMENT

DESCRIPTION

CETCO SET30 is a high strength gypsum based cement designed to set hard in a given time.

RECOMMENDED USE

CETCO SET30 can be used to cement surface casing or pipe in air drilling applications.

CHARACTERISTICS

- ▶ Controlled setting time.
- ▶ Plugging lost circulation zones
- ▶ Provides a shear thinning/pumpable slurry
- ▶ Cementing unstable ground formations
- ▶ Reduced rig time waiting on cement to set
- ▶ Cementing casing/pipe

MIXING AND APPLICATIONS

CETCO SET30 is mixed at a ration of 8 kg of CETCO SET30 to every 5 litres of water.

Note: Temperature and water quality will effect setting time, care must be taking to ensure setting time is carefully considered.

TYPICAL PROPERTIES


Appearance	off-white powder
Bulk Density	2.50

PACKAGING

20 kg pail, 32 per pallet. All pallets are plastic-wrapped.

Fieldtech Solutions - 37 Wirraway Dr, Port Melb. VIC. 3207
03 9676 9664; sales@fieldtechsoln.com; www.fieldtechsoln.com

CETCO accepts no responsibility for the results obtained throught application of this product. CETCO reserves the right to update information without notice.

An  Company | FORM: TDS_CETCOSET30_ASIAPAC_201310_V1

